





LX Hausys America Inc. is a part of Koreanbased LX Hausys Ltd., one of the world's leading providers of building and decorative materials. Headquartered in Atlanta, GA., LX Hausys America uses the industry's most advanced technology to design beautiful and functional spaces with sustainable products. LX Hausys America's business lines include surface materials, flooring, and automotive components.

Featured Product: HIMACS Eden Plus Co

LX Hausys Ltd. has established its own environmental, safety, and health policy to grow and develop together with society. LX Hausys Ltd. strives to secure society's trust through zero-accident and eco-friendly management in recognition of the fact that environment, safety, and health management is an important factor in ensuring the company's sustainable development based on the principle of "Respecting Human Dignity". In addition, LX Hausys Ltd. has introduced management regulations covering water and air quality, chemicals, and waste management at each manufacturing facility to create harmony between the entrepreneurial activities and the environment.



EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsf.org

HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

ENVIRONMENTAL PRODUCT DECLARATION VERIFICATION

EPD Information					
Program Operator		NSF International			
Declaration Holder		LX Hausys America, Inc. 900 Circle 75 Parkway, Suite 1500 Atlanta, GA 30339			
Product: HIMACS and Viatera Functional Unit: 1m ² of product over ten year service life	Date of Issue June 2, 2022	Period of Validity 5 Years Declaration Nur EPD10096			
This EPD was independently ver International in accordance with	ified by NSF ISO 14025:				
Internal	External				
This life cycle assessment was independently verified by in accordance with ISO 14044 and the reference PCR:					
LCA Information					
Basis LCA		LX Hausys Countertop LCA April 2022			
LCA Preparer		Sustainable Solutions Corpor	ation		
This life cycle assessment was critically reviewed in accordance with ISO 14044 and ISO 21930:2017					
PCR Information					
Program Operator		NSF International			
Reference PCR		NSF PCR for Residential Cou	untertops		
Date of Issue		September 17, 2013 Extended 12 months per PCRext2021-109 valid through September 30, 2022			
PCR review was conducted by:		NSF International ncss@nsf.org			

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Product Description

For both HIMACS and Viatera product lines, the results contained within this declaration represent the general minimum and maximum case scenarios in terms of life cycle impacts. Specific variations and product thicknesses within each product line have been analyzed, and life cycle impact assessment results for any given variation of either the HIMACS or Viatera products fall within the range of results presented in this declaration.

HIMACS

HIMACS surfaces are laminate acrylic countertop surfaces. Laminate acrylic is a non-porous surface that requires no sealing. Additionally, the HIMACS products can be thermoformed to produce an unlimited variety of shapes, allowing them to be used for vertical and other applications beyond countertops. Within the HIMACS product line, there are several variations, each of which has a slightly different pattern which are available in a number of color options. The maximum available thickness of HIMACS is 12mm, however, thinner profiles are available. With durability similar to that of natural stone, HIMACS stands up to everyday scratches and endures its everyday wear and tear with higher resistance to stains, chemical, and heat. This Environmental Product Declaration covers all product lines in the HIMACS collection.

Product Classification: 06 61 16 Solid Surfacing Fabrications

Viatera

Viatera surfaces are engineered stone quartz countertop surfaces. Silica is combined with polyester resin and pigment to create a non-porous surface that requires no sealing. Each variation of the Viatera product contains different ratios of various silica sizes, used to create a unique pattern. Similar to HIMACS, each available pattern has a variety of color options achieved through the use of different colored pigments. The maximum available thickness of the Viatera product is 30mm, however, thinner profiles are available. This Environmental Product Declaration covers all product lines in the Viatera collection.

Product Classification: 12 36 61.19 Quartz Agglomerate Countertops

Manufacturing Location

HIMACS surfaces are manufactured in both Adairsville, GA, USA and Cheongju, South Korea. Viatera surfaces are manufactured exclusively in Adairsville, GA. Data were collected from both facilities, and the results presented here are representative of the production processes in both locations.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Recycled Content

Within the HIMACS product line, the Eden Collection offers surfaces that contain pre-consumer recycled content. The exact amount of pre-consumer recycled content ranges from 6% to 35% depending on product color: For more information on the recycled content of the HIMACS Eden Collection, please view the following certification documents:

https://cdn.scscertified.com/products/cert_pdfs/LXHausys_US_2022_SCS-MC-01491_s.pdf

https://cdn.scscertified.com/products/cert_pdfs/LXHausys_US_2022_SCS-MC-02322_s.pdf

https://cdn.scscertified.com/products/cert_pdfs/LXHausys_US_2022_SCS-MC-02807_s.pdf

Viatera products contain no recycled content.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Product Characteristics

The specific product characteristics / technical data for the HIMACS and Viatera products are presented below in Tables 1 and 2, respectively.

Table 1 – HIMACS Technical Data						
Property	Typical Result	Test				
Thickness	12 mm (0.47 in)	-				
Density	1.69 g/cm ³ (0.061 lb/in ³)	-				
Substrate Type	Laminate	-				
Tensile Strength	6,000 psi (41.4 MPa)	ASTM D 638				
Tensile Modulus	1.5 x 10 ⁶ psi (1.0 x 10⁴ MPa)	ASTM D 638				
Tensile Elongation	0.5%	ASTM D 638				
Flexural Strength	8,407 psi (60.0 MPa)	ASTM D 638				
Tensile Modulus	1.34 x 10 ⁶ psi (9.24 x 10 ³ MPa)	ASTM D 638				
Hardness	90 Pass (Rockwell) 65 (Barcol)	ASTM D 2583				
Thermal Expansion	1.65 x 10 ⁻⁵ mm / mm / degrees C	ASTM D 696				
Deflection Temperature (under load)	90 degrees C (194 degrees F)	ASTM D 648				
Light Resistance	Pass	NEMA LD 3.3 ISFA SST 7.1				
Wear and Cleanability	Pass	ANSI Z-124.3 ANSI Z-124.6				
Cleanability and Stain Resistance	Pass	NEMA LD 3.4 ISFA SST 3.1				
Food Contact	Pass (Indoor)	NSF 51				
Fungus Resistance	Pass	ASTM G21				
Boiling Water Resistance	Pass	NEMA LD 3.5 ISFA SST 8.1				
High Temperature Resistance	Pass	NEMA LD 3.6 ISFA SST 9.1				
Radiant Heat Resistance	Pass	NEMA LD 3.1				
Scratch Resistance	Pass	ISFA SST 6.1 NEMA LC 3.7				
Ball Impact Resistance	8 oz @ 144" - Pass	NEMA LD 3.8 ISFA SST 6.1				
Water Absorption	0.04%	ISO 4586-2 / ASTM D570				
Toxicity	66.9 grams (2.36 oz)	Pittsburgh Protocol				
Flammability - Flame Spread Index - USA	<25	ASTM E-84/UL 723: Class A				
Flammability - Smoke Development Index - USA	<25	ASTM E-84/UL 723: Class A				
Flammability - Flame Spread Index - Canada	30	ANSI/UL 723CAN/ULC-S102-10				
Flammability - Smoke Development Index - Canada	10	ANSI/UL 723CAN/ULC-S102.2				
Flammability - Europe	Class B-s1, d0	EN-13501				

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Table 2 – Viatera Technical Data					
Property	Typical Result	Test			
Thickness	30 mm (1.18 in)	-			
Density	2.31 g/cm ³ (0.083 lb/in ³)	-			
Substrate Type	Engineered Stone	-			
Tensile Strength	1,043 psi (7.19 MPa)	ASTM D 638			
Tensile Modulus	1.35 x 10 ⁶ psi (9.31 x 10 ³ MPa)	ASTM D 638			
Tensile Elongation	0.5%	ASTM D 638			
Flexural Strength	4,114 psi (28.4 MPa)	ASTM D 638			
Tensile Modulus	5.5 x 10 ⁶ psi (3.8 x 10 ⁴ MPa)	ASTM D 638			
Hardness	94/100 (Barcol)	ASTM D 2583			
Thermal Expansion	1.55<1.83 x 10 ⁻⁵ mm / mm / degrees C	ASTM E 228			
Deflection Temperature (under load)	279 degrees C (534 degrees F)	ASTM D 648			
Wear and Cleanability	Pass	ANSI Z-124.3			
	279 degrees C (534 degrees F) Pass Pass	ANSI Z-124.6			
Cleanability and Stain Resistance	Pass	NEMA LD 3.4			
		NSE 51			
Food Contact	Pass (All Types)	ANSI 61			
Fungus Resistance	Pass	ASTM G21			
Boiling Water Resistance	Pass (20 min)	NEMA LD 3.5			
	1 833 (20 11111)	ISFA SST 8.1			
High Temperature Resistance	Pass (20 min)	NEMA LD 3.6			
		ISFA 551 9.1			
Radiant Heat Resistance	Pass	NEMA LD 3.1			
Scratch Resistance	Pass	ISFA SST 6.1			
		NEMALD 3.8			
Ball Impact Resistance	8 oz @ 144" - Pass	ISFA SST 6.1			
Water Absorption	0.04%	ISO 4586-2 / ASTM D570			
Flammability - Flame Spread Index - USA	<25	ASTM E-84/UL 723: Class A			
Flammability - Smoke Development Index - USA	<25	ASTM E-84/UL 723: Class A			
Flammability - Flame Spread Index - Canada	5	ANSI/UL 723CAN/ULC-S102-10			
Flammability - Smoke Development Index - Canada	90	ANSI/UL 723CAN/ULC-S102.2			

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





Featured Product: HIMACS Eden Plus Collection

Functional Unit

The functional unit for this study is one square meter of countertop surface area with a service life of ten years, including end-of-life disposition. Table 3 below summarizes the functional unit for the HIMACS and Viatera products and provides a scaling factor to one kilogram.

Table 3 – HIMACS and Viatera Functional Unit						
Parameter HIMACS Viatera						
Functional Unit (m ²)	1	1				
Service Life (years)	10	10				
Weight per Functional Unit (kg)	20.0	69.3				
Ratio to 1 kg	0.050	0.014				

(() System Boundaries

The system boundary of the LX Hausys Countertop LCA is presented below in Figure 1.



Figure 1 – HIMACS and Viatera System Boundary

Waste Management

The treatment of waste throughout this study follows the most current version of the US Environmental Protection Agency's (EPA) Waste Reduction Model (WARM). According to this model, the average municipal solid waste

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

disposition is 80% landfill and 20% incineration. This assumption is followed throughout this study in the absence of primary disposal data, with the exception of the construction stage where primary data were available.

Allocation Rules

The manufacturing facility in Adairsville, GA produces both HIMACS and Viatera countertops for LX Hausys. In addition, HIMACS surfaces are also produced in a facility located in Cheongju, South Korea. Both the Adairsville, GA and Cheongju, South Korea facilities produce surfaces of variable thickness, so allocation was conducted on a mass basis to capture variations in product size. In the Adairsville facility, the HIMACS and Viatera production lines are metered separately; therefore, no allocation was required to separate the production of the two product types.

For recycled materials, the recycled content methodology was applied.

Calculation Rules and Data Quality Requirements

SimaPro v9.2 Software System for Life Cycle Engineering, an internationally recognized LCA modeling software program, was used for life cycle impact assessment modeling. In the absence of primary data, representative secondary datasets were utilized. The two datasets used in this study were the ecoinvent Version 3 database and the USLCI database. The data used in this study meet all data quality requirements as outlined in the PCR. Secondary data were evaluated with regards to precision, completeness, consistency, reproducibility, representativeness and uncertainty. Based on these criteria, the data quality used throughout this study is considered high.

Cut-off rules were followed as defined by ISO 14044. Processes whose total contribution to the final result, with respect to their mass and in relation to all considered impact categories, is less than 1% can be neglected. The sum of the neglected processes may not exceed 5% by mass of the considered impact categories. All hazardous and toxic materials and substances were included in the life cycle inventory. This EPD is in compliance with the cut-off criteria. Capital items for the production processes (machine, buildings, etc.) were not taken into consideration.

Life Cycle Assessment Stages

The following life cycle assessment stages were considered in this study:

- Raw Material Acquisition & Pre-processing
- Construction
- Installation
- Use
- End-of-Life (Disposal)

The following sections provide a more detailed description of each considered life cycle stage.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





Raw Material Acquisition Stage

The raw material acquisition stage considers the upstream production and sourcing of raw materials used in the countertops. This stage begins when the material is extracted from the environment and ends when the material reaches the gate of the countertop construction facility. The material content of the HIMACS and Viatera products are presented below, using generalized names and percent ranges to protect proprietary information.

Percent Composit HIMACS Raw Material Weight					
Methyl Methacrylate (MMA)	20% - 30%				
Methacrylic Polymer (PMMA)	5% - 10%				
Aluminum Hydroxide	35% - 60%				
Initiators, Pigments, and Other Additives	0% - 20%				

Table 4 – HIMACS Material Composition

lable 5 – vlatera Mater	ial composition
Viatera Raw Material	Percent Composition by Weight
Crystalline Silica (Quartz)	80% - 95%
Polyester Resin Solution	5% - 15%
Initiators, Pigments, and Other Additives	0% - 5%

Vistore Meterial Composition In Law Pr

No hazardous substances were identified within these products.

In addition to the upstream production of these materials, this life cycle stage also considers the transportation of the raw materials to the LX Hausys facilities. Proprietary supplier data were collected to facilitate these freight calculations which come from a variety of suppliers utilizing transport by both truck and ship.



Construction Stage

Both HIMACS and Viatera surfaces are manufactured using processes such as mixing of raw ingredients, heat curing, cutting of the surface to shape, and sanding and polishing of the surface. Primary data were used from the 2020 calendar year to determine the inputs and outputs to the manufacturing process. All transport of support materials to the manufacturing facility and transport of waste to its disposal site is considered in the construction stage. Disposal impacts from manufacturing waste are also considered in the construction stage.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org Date of Issue: June 2, 2022 Period of Validity: 5 years Declaration#: EPD10096

HIMACS and Viatera by L>

Featured Product: HIMACS Eden Plus Colle

Hausys



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection



Figure 2 – Manufacturing Process Flow

Installation Stage

.

The installation stage starts with the product leaving the production facility and ends when the product reaches the consumer. Included in this stage are the distribution and warehousing, along with the installation of the product. Primary data were provided regarding product warehousing and distribution, and these data are proprietary and undisclosed in this EPD. All transport of the product between the manufacturing site, warehousing locations, and final installation site are considered in this stage, along with the scrap created during the installation process. Products produced at the Adairsville facility are transported to a warehouse for storage before distribution. The warehouse is located around 15 km from the manufacturing site and products are transported by truck. Products produced in the United States are distributed across North America with an average transportation distance of around 1466 km by truck and 129 km by ship. Products produced in South Korea are distributed across Europe and Asia with an average transportation distance of around 1775 km by truck and 9918 km by ship.

In addition to the warehousing and distribution, this stage also considers the installation of the countertop product. Installation involves cutting, sanding, and securing the surface in place with adhesive and caulk, along with the disposal of any scrap created during installation. A 10% scrap rate was chosen based on data from and conversations with LX Hausys personnel. Based on these assumptions, the following installation inventories were used for HIMACS and Viatera products, respectively:

Input	Quantity	Unit (per m ²)					
Silicone Adhesive	0.10	kg					
Silicone Caulk	0.25	kg					
Electricity	0.05	kWh					
Install Scrap Disposal	2.0	kg					

Table 6 – HIMACS Installation Inventory

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



Featured Product: HIMACS Eden Plus Collectio

Table 7 – Viatera Installation Inventory					
Input	Quantity	Unit (per m ²)			
Silicone Adhesive	0.10	kg			
Silicone Caulk	0.25	kg			
Electricity	0.05	kWh			
Install Scrap Disposal	6.9	kg			

Use	Sta	ge
-----	-----	----

Considered in the use stage is the daily maintenance of the countertop across the ten year service life. Identical maintenance assumptions are used for HIMACS and Viatera products. Table 8 below details the assumed maintenance inventory for one square meter of installed countertop over a period of ten years.

Table 8 – HIMACS and Viatera Maintenance Inventory

Input	Quantity	Unit (per m ²)
Water	110	kg
Detergent	2.74	kg



Disposal Stage

HIMACS and Viatera surfaces are not typically recycled or reused at the end of life. As such, disposal was modeled as 80% landfill and 20% incineration, according to the most current version of the US EPA WARM. The transportation distance at end of life is assumed to be 100 kilometers. These assumptions are used for both the Adairsville, GA and the Cheongju, South Korea sites.



Life Cycle Assessment (LCA)

This section presents the life cycle impact assessment (LCIA) results for both HIMACS and Viatera surfaces across the full cradle to grave life cycle of these products. All results presented in this section are impacts per functional unit: one square meter of countertop over a period of ten years.

HIMACS TRACI 2.1

Tables 9 and 10 below represent the cradle to grave life cycle impact assessment results for the HIMACS products with the respective highest and lowest results according to the TRACI 2.1 impact assessment methodology. The highest and lowest impact products were chosen based off of overall trends in results.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Impact Category	Unit (per m²)	Raw Material Acquisition	Construction	Installation	Use	Disposal	Total
Global Warming	kg CO ₂ eq	7.84E+01	1.40E+01	6.35E+00	4.42E+01	2.41E+00	1.45E+02
Acidification	kg SO₂ eq	4.47E-01	1.16E-01	2.00E-02	1.50E-01	5.09E-03	7.39E-01
Smog	kg O₃ eq	6.45E+00	7.37E-01	2.84E-01	1.88E+00	1.32E-01	9.48E+00
Eutrophication	kg N eq	1.30E-01	5.81E-03	2.47E-02	2.47E+00	3.11E-03	2.63E+00
Ozone Depletion	kg CFC-11 eq	1.59E-06	1.65E-07	1.43E-06	2.71E-06	5.09E-08	5.96E-06
Fossil Fuel Depletion*	MJ surplus	1.64E+02	1.75E+01	9.07E+00	1.19E+01	9.39E-01	2.04E+02

Table 9 – HIMACS Maximum Case Scenario TRACI 2.1 Cradle to Grave LCIA

Table 10 – HIMACS Minimum Case Scenario TRACI 2.1 Cradle to Grave LCIA

	Unit	Raw Material					
Impact Category	(per m ²)	Acquisition	Construction	Installation	Use	Disposal	Total
Global Warming	kg CO ₂ eq	5.51E+01	4.54E+00	8.61E+00	4.42E+01	2.41E+00	1.15E+02
Acidification	kg SO₂ eq	2.92E-01	2.76E-02	6.66E-02	1.50E-01	5.09E-03	5.42E-01
Smog	kg O₃ eq	3.11E+00	2.28E-01	9.93E-01	1.88E+00	1.32E-01	6.34E+00
Eutrophication	kg N eq	9.23E-02	2.69E-02	2.50E-02	2.47E+00	3.11E-03	2.62E+00
Ozone Depletion	kg CFC-11 eq	1.41E-06	1.61E-07	1.96E-06	2.71E-06	5.09E-08	6.29E-06
Fossil Fuel Depletion*	MJ surplus	1.14E+02	4.04E+00	1.36E+01	1.19E+01	9.39E-01	1.44E+02

* TRACI 2.1 methodology does not currently contain a comprehensive Abiotic Depletion Potential category. Instead, impacts are reported using the Fossil Fuel Depletion impact category, which assesses the use of non-renewable fuel resources throughout the product life cycle.

HIMACS Interpretation

The TRACI 2.1 results presented above were analyzed to understand the trends across the full cradle to grave life cycle of the HIMACS products. Figures 3 and 4 below show the contribution of each HIMACS life cycle stage to the overall impacts in each of the considered TRACI 2.1 impact categories.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection



Figure 3 – HIMACS Maximum Case Scenario TRACI 2.1 Impact Analysis



Figure 4 - HIMACS Minimum Case Scenario TRACI 2.1 Impact Analysis

For this HIMACS product, raw material acquisition is the primary driver of environmental impacts in all considered impact categories with two exceptions. In the eutrophication and ozone depletion impact categories, product use is the dominant contributor. Raw material impacts are driven by methyl methacrylate and aluminum hydroxide used in the product recipe, the ingredients that contribute most to the product's mass. The impact from the use stage comes from the use of soap for daily product maintenance over the course of ten years.

The use stage is the secondary driver of impacts in the global warming, acidification, and smog categories. The installation stage is the secondary driver of impacts in the ozone depletion category. The construction stage is the

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

secondary driver of fossil fuel depletion in the maximum case scenario and installation is the secondary driver of fossil fuel depletion in the minimum case scenario.

Viatera TRACI 2.1

Tables 11 and 12 below represents the cradle to grave life cycle impacts assessment results for the Viatera products with the respective highest and lowest results according to the TRACI 2.1 impact assessment methodology. The highest and lowest impact products were chosen based off of overall trends in results.

		Raw					
Impact Category	Unit (per m ²)	Material Acquisition	Construction	Installation	Use	Disposal	Total
Global Warming	kg CO ₂ eq	1.10E+02	2.88E+01	1.91E+01	4.41E+01	8.32E+00	2.11E+02
Acidification	kg SO₂ eq	6.11E-01	2.26E-01	5.64E-02	1.50E-01	1.76E-02	1.06E+00
Smog	kg O₃ eq	1.27E+01	1.64E+00	8.09E-01	1.88E+00	4.57E-01	1.74E+01
Eutrophication	kg N eq	2.50E-01	2.14E-02	7.77E-02	2.47E+00	1.07E-02	2.83E+00
Ozone Depletion	kg CFC-11 eq	9.77E-06	8.17E-07	3.26E-06	2.71E-06	1.76E-07	1.67E-05
Fossil Fuel Depletion*	MJ surplus	2.04E+02	3.99E+01	2.68E+01	1.19E+01	3.25E+00	2.86E+02

Table 12 - Viatera Minimum TRACI 2.1 Cradle to Grave LCIA

Impact Category	Unit (per m²)	Raw Material Acquisition	Construction	Installation	Use	Disposal	Total
Global Warming	kg CO ₂ eq	7.99E+01	2.88E+01	1.93E+01	4.42E+01	8.33E+00	1.81E+02
Acidification	kg SO ₂ eq	5.17E-01	2.26E-01	5.65E-02	1.50E-01	1.76E-02	9.68E-01
Smog	kg O₃ eq	1.17E+01	1.64E+00	8.12E-01	1.88E+00	4.57E-01	1.65E+01
Eutrophication	kg N eq	1.68E-01	2.15E-02	7.94E-02	2.47E+00	1.07E-02	2.75E+00
Ozone Depletion	kg CFC-11 eq	6.27E-06	8.17E-07	3.26E-06	2.71E-06	1.76E-07	1.32E-05
Fossil Fuel Depletion*	MJ surplus	1.46E+02	3.99E+01	2.68E+01	1.19E+01	3.25E+00	2.28E+02

* TRACI 2.1 methodology does not currently contain a comprehensive Abiotic Depletion Potential category. Instead, impacts are reported using the Fossil Fuel Depletion impact category, which assesses the use of non-renewable fuel resources throughout the product life cycle.

Viatera Interpretation

The TRACI 2.1 results presented above were analyzed to understand the trends across the full cradle to grave life cycle of the Viatera products. Figures 5 and 6 below shows the contribution of each Viatera life cycle stage to the overall impacts in each of the considered TRACI 2.1 impact categories.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

100% 90% 80% 70% 60% 50% 40% 30% 20% 10% 0% **Global Warming** Acidification Smog Eutrophication **Ozone Depletion** Fossil Fuel Depletion Use Raw Material Acquisition Construction Installation Disposal

Figure 5 – Viatera Maximum TRACI 2.1 Impact Analysis



Figure 6 - Viatera Minimum TRACI 2.1 Impact Analysis

For the Viatera product, raw material acquisition is the primary driver of environmental impact in all considered impact categories with one exception. In the eutrophication impact category, product use is the dominant contributor. Raw material impacts are driven by the polyester resin solution used in the product recipe. Although silica is the largest contributor to the product's mass, silica has a lower environmental impact; thus, the polyester resin is the largest driver of raw material impacts. The impact from the use stage comes from the use of soap for daily product maintenance over the course of ten years.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

The use stage is the secondary driver of impacts in the global warming and smog categories, while the installation stage is the secondary contributor in the ozone depletion category, and the construction stage is the secondary contributor in the acidification and fossil fuel depletion categories.

CML

In addition to the LCIA results reported above using the TRACI 2.1 methodology, LCIA results were also calculated using the CML v3.06 impact assessment methodology. Tables 13 through 16 below represent the cradle to grave life cycle impact assessment results for the HIMACS and Viatera products according to the CML impact assessment methodology.

	Raw								
Impact Category	Unit (per m ²)	Material Acquisition	Construction	Installation	Use	Disposal	Total		
Global Warming	kg CO ₂ eq	7.97E+01	1.42E+01	6.70E+00	4.47E+01	2.40E+00	1.48E+02		
Acidification	kg SO ₂ eq	4.45E-01	1.27E-01	1.94E-02	1.34E-01	3.97E-03	7.29E-01		
Photochemical Ozone Creation	kg C ₂ H ₄ eq	3.07E-02	5.64E-03	1.23E-03	2.67E-02	-4.71E-04	6.38E-02		
Eutrophication	kg PO₄ eq	7.78E-02	5.53E-03	1.07E-02	1.06E+00	1.90E-03	1.16E+00		
Ozone Depletion	kg CFC-11 eq	1.37E-06	1.32E-07	1.23E-06	2.47E-06	3.93E-08	5.24E-06		
Abiotic Depletion (elements)	kg Sb eq	1.56E-04	1.08E-05	1.67E-05	3.46E-04	5.67E-07	5.30E-04		
Abiotic Depletion (fossil fuel)	MJ	1.22E+03	2.07E+02	7.36E+01	1.40E+02	7.00E+00	1.65E+03		

Table 14 – HIMACS Minimum CML Cradle to Grave LCIA

Impact Category	Unit (per m²)	Raw Material Acquisition	Construction	Installation	Use	Disposal	Total
Global Warming	kg CO ₂ eq	5.60E+01	4.59E+00	8.86E+00	4.47E+01	2.40E+00	1.17E+02
Acidification	kg SO₂ eq	3.05E-01	2.95E-02	6.09E-02	1.34E-01	3.97E-03	5.33E-01
Photochemical Ozone Creation	kg C ₂ H ₄ eq	2.81E-02	1.67E-03	2.42E-03	2.67E-02	-4.71E-04	5.84E-02
Eutrophication	kg PO₄ eq	4.99E-02	1.22E-02	1.54E-02	1.06E+00	1.90E-03	1.14E+00
Ozone Depletion	kg CFC-11 eq	1.19E-06	1.30E-07	1.63E-06	2.47E-06	3.93E-08	5.46E-06
Abiotic Depletion (elements)	kg Sb eq	1.05E-04	2.12E-05	1.91E-05	3.46E-04	5.67E-07	4.91E-04
Abiotic Depletion (fossil fuel)	MJ	8.53E+02	5.63E+01	1.00E+02	1.40E+02	7.00E+00	1.16E+03

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

	Unit	Raw Material						
Impact Category	(per m ²)	Acquisition	Construction	Installation	Use	Disposal	Total	
Global Warming	kg CO ₂ eq	1.09E+02	2.91E+01	2.03E+01	4.47E+01	8.31E+00	2.12E+02	
Acidification	kg SO ₂ eq	5.50E-01	2.44E-01	5.48E-02	1.34E-01	1.37E-02	9.96E-01	
Photochemical Ozone Creation	kg C₂H₄ eq	4.37E-02	1.19E-02	3.49E-03	2.67E-02	-1.63E-03	8.42E-02	
Eutrophication	kg PO₄ eq	1.62E-01	1.54E-02	3.30E-02	1.06E+00	6.55E-03	1.28E+00	
Ozone Depletion	kg CFC-11 eq	8.88E-06	7.17E-07	2.60E-06	2.47E-06	1.36E-07	1.48E-05	
Abiotic depletion (elements)	kg Sb eq	8.03E-04	3.71E-05	3.45E-05	3.46E-04	1.96E-06	1.22E-03	
Abiotic Depletion (fossil fuel)	MJ	1.67E+03	4.39E+02	2.13E+02	1.40E+02	2.42E+01	2.49E+03	
Table 16 Vistore Minimum CML Cradle to Crave LCIA								

Table 15 – Viatera Maximum CML Cradle to Grave LCIA

Table 16 - Viatera Minimum CML Cradle to Grave LCIA

Impact Category	Unit (per m²)	Raw Material Acquisition	Construction	Installation	Use	Disposal	Total
Global Warming	kg CO ₂ eq	7.93E+01	2.91E+01	2.04E+01	4.47E+01	8.31E+00	1.82E+02
Acidification	kg SO ₂ eq	4.54E-01	2.44E-01	5.49E-02	1.34E-01	1.37E-02	9.01E-01
Photochemical Ozone Creation	kg C₂H₄ eq	3.32E-02	1.19E-02	3.51E-03	2.67E-02	-1.63E-03	7.36E-02
Eutrophication	kg PO₄ eq	1.22E-01	1.54E-02	3.36E-02	1.06E+00	6.55E-03	1.24E+00
Ozone Depletion	kg CFC-11 eq	5.66E-06	7.17E-07	2.60E-06	2.47E-06	1.36E-07	1.16E-05
Abiotic depletion (elements)	kg Sb eq	4.97E-04	3.71E-05	3.45E-05	3.46E-04	1.96E-06	9.17E-04
Abiotic Depletion (fossil fuel)	MJ	1.18E+03	4.39E+02	2.13E+02	1.40E+02	2.42E+01	2.00E+03

Material Resources

This section presents the material resource use for both HIMACS and Viatera surfaces across the full cradle to grave life cycle of these products. All resource use results are presented in this section per functional unit: one square meter of countertop over a period of ten years. These numbers are representative of the most impactful product variation in each product line.

Table 17 – HIMACS Material Resource Use								
	Raw Material							
Material Resource Category	Acquisition	Construction	Install	Use	Disposal	Total		
Virgin Renewable Resources (kg)	0.00E+00	6.08E-02	0.00E+00	0.00E+00	0.00E+00	6.08E-02		
Recycled Resources (kg)	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00		
Virgin Non-renewable Resources (kg)	2.48E+01	1.28E-02	3.50E-01	2.91E+00	0.00E+00	2.81E+01		

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

l able 18 – Vlatera Material Resource Use								
	Raw Material							
Material Resource Category	Acquisition	Construction	Install	Use	Disposal	Total		
Virgin Renewable Resources (kg)	0.00E+00	4.72E-02	0.00E+00	0.00E+00	0.00E+00	4.72E-02		
Recycled Resources (kg)	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00		
Virgin Non-renewable Resources (kg)	9.36E+01	1.62E-02	3.50E-01	2.91E+00	0.00E+00	9.68E+01		
Perometers to be Declared in the EDD								

Parameters to be Declared in the EPD

The following life cycle inventory (LCI) data are included, highlighting the material and energy flows throughout the product life cycle of both the HIMACS and Viatera products. These numbers are representative of the most and least impactful product variation in each product line.

Inventory Assessment Category Emissions to Air (kg)	Raw Material Acquisition	Construction	Installation	Use	Disposal	Total
SOx	2.64E-01	9.34E-02	1.13E-02	3.95E-02	7.66E-04	4.09E-01
NO _X	3.13E-01	3.13E-02	1.15E-02	7.15E-02	5.36E-03	4.33E-01
CO ₂	6.79E+01	1.33E+01	5.75E+00	1.27E+02	5.35E+00	2.19E+02
CH ₄	4.27E-01	4.33E-02	6.70E-02	1.92E-01	6.47E-04	7.29E-01
N ₂ O	1.12E-02	3.64E-04	2.17E-04	1.52E-04	1.04E-02	2.23E-02
СО	1.45E-01	1.15E-02	1.01E-02	1.79E-01	2.42E-03	3.48E-01
Water Usage and Emissions to Water (kg)						
Phosphates	2.43E-02	1.25E-03	1.82E-03	7.47E-01	5.00E-04	7.75E-01
Nitrates	7.05E-03	5.34E-04	8.40E-03	8.11E-01	6.70E-04	8.28E-01
Dioxin	1.47E-17	4.60E-18	2.13E-17	7.34E-17	2.77E-19	1.14E-16
Arsenic	3.68E-04	5.18E-06	7.91E-06	6.73E-05	6.23E-06	4.55E-04
Lead	3.08E-04	2.65E-05	1.60E-03	8.50E-04	1.14E-03	3.93E-03
Water Usage and Emissions to Water (kg)						
Mercury	2.29E-06	1.27E-07	4.14E-06	2.54E-06	2.00E-07	9.30E-06
Cadmium	9.86E-06	1.21E-06	3.38E-05	4.06E-05	2.83E-06	8.83E-05
Chromium	2.33E-03	2.25E-05	3.55E-05	3.72E-04	1.92E-05	2.78E-03
Water Consumption	1.52E+04	1.01E+03	1.80E+03	1.00E+05	2.56E+02	1.19E+05
Energy Type and Usages (MJ)						
Primary Energy Demand	1.40E+03	3.00E+02	8.31E+01	3.23E+02	7.57E+00	2.11E+03
Fossil Fuel Based Energy	1.32E+03	2.24E+02	7.87E+01	1.51E+02	7.45E+00	1.78E+03
Nuclear Energy	6.57E+01	1.48E+00	2.27E+00	1.96E+01	5.95E-02	8.92E+01

Table 19 – HIMACS Maximum LCI Parameters

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Energy Type and Usages (MJ)						
Solar Energy	2.56E-03	4.29E-04	3.15E-03	2.03E-01	9.69E-05	2.09E-01
Wind Energy	7.48E-01	1.45E-01	2.14E-01	2.20E+00	6.46E-03	3.31E+00
Hydro Energy	6.43E+00	6.25E-01	1.09E+00	8.80E+00	3.17E-02	1.70E+01
Biomass Energy	6.78E+00	7.39E+01	8.52E-01	1.41E+02	1.96E-02	2.23E+02
Waste Management (kg)						
Incineration Without Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Incineration With Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.01E+00	0.00E+00
Landfill (non-hazardous)	4.81E+00	8.69E+00	2.00E+00	0.00E+00	1.60E+01	3.15E+01
Hazardous Waste	0.00E+00	2.47E-02	0.00E+00	0.00E+00	0.00E+00	2.47E-02
Landfill Avoidance (recycling)	0.00E+00	7.01E-02	0.00E+00	0.00E+00	0.00E+00	7.01E-02

Table 20 - HIMACS Minimum LCI Parameters										
Inventory Assessment Category	Raw Material					—				
Emissions to Air (kg)	Acquisition	Construction	Install	Use	Disposal	Total				
SOx	2.04E-01	2.07E-02	3.42E-02	3.93E-02	7.63E-04	2.99E-01				
NOx	1.22E-01	8.94E-03	3.85E-02	7.01E-02	5.23E-03	2.45E-01				
CO ₂	1.00E-01	2.54E-02	4.46E-01	7.23E-02	7.59E-04	6.44E-01				
CH4	3.28E-01	9.98E-03	6.87E-02	1.92E-01	6.47E-04	5.99E-01				
N ₂ O	1.13E-03	9.06E-05	2.79E-04	1.05E-02	1.97E-04	1.22E-02				
СО	9.43E-02	3.71E-03	1.22E-02	1.79E-01	2.42E-03	2.92E-01				
Water Usage and Emissions to Water (kg)										
Phosphates	1.76E-02	1.05E-02	2.67E-03	7.47E-01	5.00E-04	7.79E-01				
Nitrates	6.88E-03	3.55E-03	8.83E-03	8.11E-01	6.70E-04	8.31E-01				
Dioxin	9.74E-18	1.05E-17	2.20E-17	7.34E-17	2.77E-19	1.16E-16				
Arsenic	2.45E-04	1.79E-05	9.81E-06	6.71E-05	6.15E-06	3.46E-04				
Lead	2.14E-04	4.94E-05	1.63E-03	8.45E-04	1.14E-03	3.88E-03				
Mercury	1.76E-03	9.01E-04	4.29E-03	2.54E-03	2.00E-04	9.69E-03				
Cadmium	7.09E-06	3.21E-06	3.46E-05	4.06E-05	2.83E-06	8.84E-05				
Chromium	1.18E-03	3.12E-05	4.07E-05	2.83E-04	1.49E-05	1.55E-03				
Water Consumption	1.17E+04	1.41E+03	1.91E+03	1.00E+05	2.56E+02	1.16E+05				
Energy Type and Usages (MJ)										
Primary Energy Demand	9.97E+02	1.12E+02	1.14E+02	3.23E+02	7.57E+00	1.55E+03				
Fossil Fuel Based Energy	9.31E+02	6.12E+01	1.07E+02	1.51E+02	7.45E+00	1.26E+03				
Nuclear Energy	5.30E+01	2.95E+01	3.61E+00	1.96E+01	5.95E-02	1.06E+02				

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Energy Type and Usages (MJ)						
Solar Energy	3.41E-03	5.03E-01	5.19E-03	2.87E-01	1.38E-04	7.98E-01
Wind Energy	6.29E-01	5.34E-01	3.83E-01	2.31E+00	6.77E-03	3.86E+00
Hydro Energy	5.16E+00	2.52E+00	1.57E+00	8.80E+00	3.17E-02	1.81E+01
Biomass Energy	7.46E+00	1.74E+01	9.93E-01	1.41E+02	1.96E-02	1.67E+02
Waste Management (kg)						
Incineration Without Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Incineration With Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.01E+00	0.00E+00
Landfill (non-hazardous)	4.81E+00	8.69E+00	2.00E+00	0.00E+00	1.60E+01	3.15E+01
Hazardous Waste	0.00E+00	2.47E-02	0.00E+00	0.00E+00	0.00E+00	2.47E-02
Landfill Avoidance (recycling)	0.00E+00	7.01E-02	0.00E+00	0.00E+00	0.00E+00	7.01E-02

Table 21 – Viatera Maximum LCI Parameters

Inventory Assessment Category Emissions to Air (kg)	Raw Material Acquisition	Construction	Installation	Use	Disposal	Total
SOx	2.47E-01	1.76E-01	3.17E-02	3.95E-02	2.65E-03	4.97E-01
NOx	4.96E-01	6.42E-02	3.25E-02	7.01E-02	1.85E-02	6.81E-01
CO ₂	8.65E+01	2.76E+01	1.71E+01	1.27E+02	1.85E+01	2.76E+02
CH ₄	3.28E-01	8.86E-02	2.18E-01	1.92E-01	2.24E-03	8.29E-01
N ₂ O	6.33E-02	2.48E-04	6.39E-04	1.05E-02	6.82E-04	7.54E-02
СО	3.14E-01	2.92E-02	2.96E-02	1.79E-01	8.37E-03	5.60E-01
Water Usage and Emissions to Water (kg)						
Phosphates	5.57E-02	4.84E-03	4.06E-03	7.47E-01	1.73E-03	8.14E-01
Nitrates	2.19E-02	3.13E-03	2.79E-02	8.11E-01	2.32E-03	8.67E-01
Dioxin	1.29E-13	3.43E-14	2.56E-14	7.34E-14	9.56E-16	2.63E-13
Arsenic	2.00E-04	1.68E-05	2.07E-05	6.73E-05	2.15E-05	3.26E-04
Water Usage and Emissions to Water (kg)						
Lead	1.76E-03	1.00E-04	5.39E-03	8.50E-04	3.95E-03	1.21E-02
Mercury	7.24E-06	5.11E-07	1.39E-05	2.71E-06	7.07E-07	2.51E-05
Cadmium	5.25E-05	4.58E-06	1.13E-04	4.08E-05	9.83E-06	2.21E-04
Chromium	6.39E-01	7.58E-02	1.07E-01	3.72E-01	6.65E-02	1.26E+00
Water Consumption	5.23E+04	3.54E+03	2.37E+03	1.00E+05	8.85E+02	1.60E+05

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Energy Type and Usages (MJ)						
Primary Energy Demand	1.93E+03	6.84E+02	2.34E+02	3.23E+02	3.17E+03	1.93E+03
Fossil Fuel Based Energy	1.80E+03	4.74E+02	2.27E+02	1.51E+02	2.65E+03	1.80E+03
Nuclear Energy	7.16E+01	6.34E+00	3.99E+00	1.96E+01	1.02E+02	7.16E+01
Solar Energy	1.80E-01	1.25E-02	5.53E-03	3.61E-03	2.02E-01	1.80E-01
Wind Energy	2.03E+01	1.27E+01	1.68E+00	5.36E-01	3.52E+01	2.03E+01
Hydro Energy	2.94E+01	2.34E+00	1.89E+00	8.80E+00	4.24E+01	2.94E+01
Biomass Energy	2.81E+01	2.01E+02	1.20E+00	1.41E+02	3.72E+02	2.81E+01
Waste Management (kg)						
Incineration Without Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Incineration With Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.39E+01	1.39E+01
Landfill (non-hazardous)	2.43E+01	1.56E+01	6.93E+00	0.00E+00	5.54E+01	1.02E+02
Hazardous Waste	0.00E+00	1.66E-01	0.00E+00	0.00E+00	0.00E+00	1.66E-01
Landfill Avoidance (recycling)	0.00E+00	1.04E-01	0.00E+00	0.00E+00	0.00E+00	1.04E-01
	11. 00 N/ M					

Table 22 - Viatera Minimum LCI Parameters

Inventory Assessment Category	Raw Material	Construction	Install		Disposal	Total
	2.47E-01	1 76E-01	3 17E-02	3 95E-02	2.65E-03	4 97E-01
SOx	2.47 - 01	1.702 01	0.17 2 02	0.002 02	2.001 00	4.57 - 01
NOx	4.96E-01	6.42E-02	3.25E-02	7.01E-02	1.85E-02	6.81E-01
CO ₂	8.65E+01	2.76E+01	1.71E+01	1.27E+02	1.85E+01	2.76E+02
CH4	3.28E-01	8.86E-02	2.18E-01	1.92E-01	2.24E-03	8.29E-01
N ₂ O	6.33E-02	2.48E-04	6.39E-04	1.05E-02	6.82E-04	7.54E-02
СО	3.14E-01	2.92E-02	2.96E-02	1.79E-01	8.37E-03	5.60E-01
Water Usage and Emissions to Water (kg)						
Phosphates	5.57E-02	4.84E-03	4.06E-03	7.47E-01	1.73E-03	8.14E-01
Nitrates	2.19E-02	3.13E-03	2.79E-02	8.11E-01	2.32E-03	8.67E-01
Dioxin	1.29E-13	3.43E-14	2.56E-14	7.34E-14	9.56E-16	2.63E-13
Arsenic	2.00E-04	1.68E-05	2.07E-05	6.73E-05	2.15E-05	3.26E-04
Lead	1.76E-03	1.00E-04	5.39E-03	8.50E-04	3.95E-03	1.21E-02
Mercury	7.24E-06	5.11E-07	1.39E-05	2.71E-06	7.07E-07	2.51E-05
Cadmium	5.25E-05	4.58E-06	1.13E-04	4.08E-05	9.83E-06	2.21E-04
Chromium	6.39E-01	7.58E-02	1.07E-01	3.72E-01	6.65E-02	1.26E+00
Water Consumption	5.23E+04	3.54E+03	2.37E+03	1.00E+05	8.85E+02	1.60E+05

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





Featured Product: HIMACS Eden Plus Collection

Energy Type and Usages (MJ)						
Primary Energy Demand	1.93E+03	6.84E+02	2.34E+02	3.23E+02	3.17E+03	1.93E+03
Fossil Fuel Based Energy	1.80E+03	4.74E+02	2.27E+02	1.51E+02	2.65E+03	1.80E+03
Nuclear Energy	7.16E+01	6.34E+00	3.99E+00	1.96E+01	1.02E+02	7.16E+01
Solar Energy	1.80E-01	1.25E-02	5.53E-03	3.61E-03	2.02E-01	1.80E-01
Wind Energy	2.03E+01	1.27E+01	1.68E+00	5.36E-01	3.52E+01	2.03E+01
Hydro Energy	2.94E+01	2.34E+00	1.89E+00	8.80E+00	4.24E+01	2.94E+01
Biomass Energy	2.81E+01	31E+01 2.01E+02		1.41E+02	3.72E+02	2.81E+01
Waste Management (kg)						
Incineration Without Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Incineration With Energy Recovery	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.39E+01	1.39E+01
Landfill (non-hazardous)	2.43E+01	1.56E+01	6.93E+00	0.00E+00	5.54E+01	1.02E+02
Hazardous Waste	0.00E+00	1.66E-01	0.00E+00	0.00E+00	0.00E+00	1.66E-01
Landfill Avoidance (recycling)	0.00E+00	1.04E-01	0.00E+00	0.00E+00	0.00E+00	1.04E-01



Other Environmental Information

Material Ingredient Reporting

In addition to the environmental impact data contained within the declaration, LX Hausys has also published Health Product Declarations (HPDs) for both the HIMACS and Viatera surfaces. The declarations can be accessed via the <u>HPD Public Repository</u>.

Disclaimer

Comparability of EPDs is limited to those applying a functional unit. EPDs are comparable only if they comply with this document, use the same sub-category PCR where applicable, include all relevant information modules and are based on equivalent scenarios with respect to the context of construction works. This EPD was not written to support comparative assertions. Even for similar products, differences in functional unit, use and end-of-life stage assumptions, and data quality may produce incomparable results. It is not recommended to compare EPDs with another organization as there may be differences in methodology, assumptions, allocation methods, data quality such as variability in datasets, and results of variability in assessment software tools used. This declaration represents an average performance based on production values for a calendar year.

Contact Information

For additional information, please visit <u>https://www.lxhausys.com</u>. To contact LX Hausys, please visit <u>https://www.lxhausys.com/us/contactUs/pro</u>.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

) R

References

The following references were used in the publication of this EPD:

- (ILCD, 2010) Joint Research Commission, 2010, ILCD Handbook: General Guide for Life Cycle Assessment
- Intergovernmental Panel on Climate Change (IPCC)
- ISO 14025:2011-10, Environmental labels and declarations Type III environmental declarations Principles and procedures
- ISO 14040:2009-11, Environmental management Life cycle assessment Principles and framework
- ISO 14044:2006-10, Environmental management Life cycle assessment Requirements and guidelines
- ISO 9001 Quality Management System
- ISO 14001 Environmental Management System
- ISO 21930:2017, Sustainability in buildings and civil engineering works Core rules for environmental product declarations of construction products and services
- ISO 4586-2:2004, High-Pressure Decorative Laminates Sheets Made from Thermosetting Resins Part 2: Determination Of Properties
- Product Category Rule for Environmental Product Declaration PCR for Residential Countertops. NSF International. Valid through September 17, 2021
- ASTM D570 Standard Test Method for Water Absorption of Plastics
- ASTM D638 Standard Test Method for Tensile Properties of Plastics
- ASTM D2583 Standard Test Method for Indentation Hardness of Rigid Plastics by Means of a Barcol
 Impressor
- ASTM D696 Standard Test Method for Coefficient of Linear Thermal Expansion of Plastics Between -30°C and 30°C with a Vitreous Silica Dilatometer
- ASTM D648 Standard Test Method for Deflection Temperature of Plastics Under Flexural Load in the Edgewise Position
- ASTM G21 Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi
- ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials
- NEMA LD 3 High-Pressure Decorative Laminates (HPDL)
- ANSI/UL 723CAN/ULC-S102-10 Surface Burning Characteristics of Building Materials
- ANSI/NSF Standard 51 (National Sanitation Foundation Food Equipment Materials)
- ANSI Z124.3 Plastic Lavatories
- ANSI Z124.6 Plastic Sinks
- ISFA SST 3.1 Cleanability/Stain Resistance
- ISFA SST 6.1 Impact Resistance 226.8g (1/2lb.) Ball
- ISFA SST 7.1 Light Resistance
- ISFA SST 8.1 Boiling Water Resistance
- ISFA SST 9.1 High Temperature Resistance
- Pittsburgh Protocol
- EN-13501 Fire Classification of Construction Products and Building Elements
- Product Life Cycle Accounting and Reporting Standard, Greenhouse Gas Protocol, World Business Council

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

for Sustainable Development and World Resources Institute

- Countertop Life Cycle Assessment. LX Hausys / Sustainable Solutions Corporation. April 2022
- US EPA's Solid Waste Management and Greenhouse Gases: A Life-Cycle Assessment of Emissions and Sinks page 111

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



Featured Product: HIMACS Eden Plus Collection

Appendix: ISO 21930 Analysis

In order to meet ISO 21930 criteria, this EPD includes supplemental information in addition to the scope of the NSF Countertop PCR as presented in this section. Below are the life cycle assessment scenarios required by ISO 21930.

Table 23-Transport to Building Site (A4)

Name	НІМАС	S Georgia	HIMACS	South Korea	V	Unit	
Fuel type	Diesel	Heavy fuel oil	Diesel	Heavy fuel oil	Diesel	Heavy fuel oil	-
Liters of fuel	3.80E+01	2.21E+04	3.80E+01	2.21E+04	3.80E+01	2.21E+04	l/100km
Vehicle type	Truck	Ship	Truck	Ship	Truck	Ship	-
Transport distance	1.47E+03	1.29E+02	1.77E+03	9.92E+03	1.47E+03	1.29E+02	km
Capacity utilization (including empty runs, mass or volume based)	9.00E+01	9.00E+01	9.00E+01	9.00E+01	9.00E+01	9.00E+01	%
Gross density of products transported	2.00E+01	2.00E+01	2.00E+01	2.00E+01	6.93E+01	6.93E+01	kg/m ³

Table 24 – Installation into the Building (A5)

Name	HIMACS	Viatera	Unit
Silicone Adhesive	1.00E-01	1.00E-01	kg
Silicone Caulk	2.50E-01	2.50E-01	kg
Net freshwater consumption	0.00E+00	0.00E+00	m ³
Other resources	0.00E+00	0.00E+00	kg
Electricity consumption	5.00E-02	5.00E-02	kWh
Other energy carriers	0.00E+00	0.00E+00	MJ
Product loss per functional unit	2.00E+00	6.93E+00	kg
Waste materials at the construction site	0.00E+00	0.00E+00	kg
Output materials resulting from on-site waste processing	0.00E+00	0.00E+00	kg
Packaging waste, wood	6.04E-02	4.72E-02	kg
Packaging waste, cardboard	4.48E-04	0.00E+00	kg
Packaging waste, protective film	3.90E-03	8.51E-03	kg
Biogenic carbon contained in packaging	3.03E-02	2.36E-02	kg CO ₂
Direct emissions to ambient air, soil, and water	0.00E+00	0.00E+00	kg
VOC emissions	-	-	µg/m³

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Table 25 – Reference Service Life

Name	HIMACS and Viatera	Unit						
RSL	10	years						
Indoor environment	Normal building operating conditions	-						
Use conditions	Normal building operating conditions	-						
Table 26 – Maintenance (B2)								

Name	HIMACS	Viatera	Unit				
Daily Cleaning	3.65E+03	3.65E+03	Cycles/RSL				
Daily Cleaning	3.65E+03	3.65E+03	Cycles/ESL				
Net freshwater consumption specified by water source and fate	0.11, tap water, evaporated	0.11, tap water, evaporated	m ³				
Detergent	2.91E+00	2.91E+00	kg				
Other resources	0.00E+00	0.00E+00	kg				
Energy input, specified by activity, type and amount	0.00E+00	0.00E+00	kWh				
Other energy carriers specified by type	0.00E+00	0.00E+00	kWh				
Power output of equipment	0.00E+00	0.00E+00	kW				
Waste materials from maintenance	0.00E+00	0.00E+00	kg				
Direct emissions to ambient air, soil and water	0.00E+00	0.00E+00	kg				
Further assumptions for scenario development Countertops cleaned with soap and water daily over a period.							

Table 27 – End of Life (C1 – C4)

Name		HIMACS	Viatera	Unit
Assumptions for scenario development	This disposal was modeled according to the a (80% landfill, 20% incineration) according to diesel powered re	average US mun US EPA data. W efuse truck.	icipal waste di /aste is transpo	sposition orted via
Collection process	Collected separately	2.00E+01	6.93E+01	kg
Collection process	Collected with mixed construction waste	0.00E+00	0.00E+00	kg
	Reuse	0.00E+00	0.00E+00	kg
	Recycling	0.00E+00	0.00E+00	kg
Beenverv	Landfill	1.60E+01	5.54E+01	kg
Recovery	Incineration	4.01E+00	1.39E+01	kg
	Incineration with energy recovery	0.00E+00	0.00E+00	kg
	Energy conversion	-	-	-
Disposal	Product or material for final deposition	2.00E+01	6.93E+01	kg
Removals of biogenic carbon	0.00E+00	0.00E+00	kg CO ₂	

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

The system boundary and life cycle stages mandated by ISO 21930 closely follow the system boundary presented above with one difference: ISO 21930 groups the Raw Material Acquisition and Construction Stages together under the Production Stage. The PCR does not account for replacement included in module B4. All other life cycle stages are consistent between the two standards. Table 28 below shows how the life cycle stages compare between ISO 21930 and the NSF Countertop PCR.

Table 28 – System Boundary Comparison

	System Boundary																
ISO 21930 Life Cycle Stage	Produc		tion stage	Constr sta	ruction	Use stage					End	d-of-Li	fe sta	ge	Benefits and Loads Beyond the System Boundary		
Modules	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Inclusion	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	MND
Countertop PCR Life Cycle Stage	Ra Mate Acquis	w erial sition	Construction	Ins	tall		Use Disposal							Not included			
Included in System Boundary	Ye	s	Yes	Yes			Yes				Ye	s		No			

All assumptions and included flows and processes remain identical between the two system boundaries. All results are presented including the distinction between the Raw Material Acquisition and Construction Stage to show greater transparency and to meet the requirements of both standards. All modules were considered in this study, however, reported results below are only shown for modules that include non-zero values.

ISO 21930 also requires additional inventory data to be reported. Tables 29 through 32 show the use of resources and renewable primary energy across the life cycle of the HIMACS and Viatera products, respectively. All figures presented in this section are representative of the most impactful product variation in each product line per functional unit.

Table 29 – HIMACS Maximum Use of Primary and Secondary Resources

		Unit	Raw M Acqui	aterial sition	Construction	Install	
	Primary and Secondary Resource Categories	A1 A2		A3	A4	A5	
RPRE	Renewable primary energy as energy carrier	MJ	7.34E+00	0.00E+00	8.01E-01	3.80E-01	9.68E-01
RPRM	Renewable primary energy resources as material utilization		6.78E+00	0.00E+00	7.39E+01	1.33E-01	7.19E-01
NRPRE	Nonrenewable primary energy as energy carrier	MJ	1.27E+03	1.20E+02	2.21E+02	5.90E+01	2.17E+01
NRPRM	Nonrenewable primary energy as material utilization	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
SM	Use of secondary material	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Unit	Raw Material hit Acquisition		l Co	onstruction	Install		
	Primary and Secondary Resource Categories			A1 A2		2	A3	A4	A5
NRSF	Use of nonrenewable secondary fuels	MJ	0.00)E+00	0.00	E+00	0.00E+00	0.00E+00	0.00E+00
RE	Energy recovered from disposed waste	MJ	0.00)E+00	0.00	E+00	0.00E+00	0.00E+00	0.00E+00
FW	Use of net fresh water	m³	3.67	7E-01	0.00	E+00	2.44E-02	5.19E-03	4.27E-02
					Us	e	Dis	posal	Total
	Primary and Secondary Resource Categories		Unit	B2	2	B4	C2	C4	TOtal
RPRE	Renewable primary energy as energy carrier		MJ	1.17E	+01	1.49E+02	0.00E+00	3.94E-02	1.70E+02
RPRM	Renewable primary energy resources as material utilization	า	MJ	1.41E	+02	1.56E+03	0.00E+00	1.96E-02	1.78E+03
NRPRE	Nonrenewable primary energy as energy carrier		MJ	2.00E	+02	1.33E+04	3.70E+00	3.81E+00	1.52E+04
NRPRM	Nonrenewable primary energy as material utilization		MJ	0.00E	+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
SM	Use of secondary material		kg	0.00E	+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF	Use of renewable secondary fuels		MJ	0.00E	+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	Use of nonrenewable secondary fuels		MJ	0.00E	+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RE	Energy recovered from disposed waste		MJ	0.00E	+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW	Use of net fresh water		m ³	2.66E	+00	2.17E+01	0.00E+00	7.06E-03	2.48E+01

Table 30 - HIMACS Minimum Use of Primary and Secondary Resources

		Unit		Raw M Acqui	lateria sition		Construct	ion	Install	
	Primary and Secondary Resource Categories		A	\1	A	2	A3		A4	A5
RPRE	Renewable primary energy as energy carrier	MJ	5.89	E+00	0.00	E+00	3.57E+0	0	1.03E+00	9.69E-01
RPRM	Renewable primary energy resources as material utilization	MJ	7.46	E+00	0.00	E+00	1.74E+0	1	2.74E-01	7.19E-01
NRPRE	Nonrenewable primary energy as energy carrier	MJ	9.69	E+02	1.49	E+01	9.02E+0	1	8.89E+01	2.18E+01
NRPRM	Nonrenewable primary energy as material utilization	MJ	0.00	E+00	0.00	E+00	0.00E+0	0	0.00E+00	0.00E+00
SM	Use of secondary material	kg	0.00	E+00	0.00	E+00	0.00E+0	0	0.00E+00	0.00E+00
RSF	Use of renewable secondary fuels	MJ	0.00	E+00	0.00	E+00	0.00E+0	0	0.00E+00	0.00E+00
NRSF	Use of nonrenewable secondary fuels	MJ	0.00	E+00	0.00	E+00	0.00E+0	0	0.00E+00	0.00E+00
RE	Energy recovered from disposed waste	MJ	0.00	E+00	0.00	E+00	0.00E+0	0	0.00E+00	0.00E+00
FW	Use of net fresh water	m ³	2.82	2E-01	0.00	E+00	8.89E-02	2	9.04E-03	4.27E-02
					Us	e		Disp	oosal	Total
	Primary and Secondary Resource Categories		Unit	Bź	2	B4	С	2	C4	Total
RPRE	Renewable primary energy as energy carrier		MJ	1.17E	+01	1.62E+	02 0.00E	E+00	0.00E+00	1.85E+02
RPRM	Renewable primary energy resources as material utilization	۱	MJ	1.41E	+02	1.17E+(03 0.00E	E+00	0.00E+00	1.34E+03
NRPRE	Nonrenewable primary energy as energy carrier		MJ	2.00E	+02	9.74E+	03 3.70E	E+00	3.81E+00	1.11E+04
NRPRM	Nonrenewable primary energy as material utilization		MJ	0.00E	+00	0.00E+	00 0.00E	=+00	0.00E+00	0.00E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

	Ur	nit	Raw Material Acquisition		Raw Material Cons Acquisition		w Material Construction		all
	Primary and Secondary Resource Categories		A1 /	A2	A3	A4	A5		
SM	Use of secondary material	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00		
RSF	Use of renewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00		
NRSF	Use of nonrenewable secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00		
RE	Energy recovered from disposed waste	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00		
FW	Use of net fresh water	m ³	2.66E+00	2.16E+01	0.00E+00	0.00E+00	2.46E+01		

Table 31 – Viatera Maximum Use of Primary and Secondary Resources

		Unit	t Acquisition		al Cor	struction	Install	
	Primary and Secondary Resource Categories		A1	A	2	A3	A4	A5
RPRE	Renewable primary energy as energy carrier	MJ	3.62E+01	0.00	E+00 3.	03E+00	1.31E+00	1.06E+00
RPRM	Renewable primary energy resources as material utilization	MJ	2.81E+01	0.00	E+00 2.	01E+02	4.59E-01	7.42E-01
NRPRE	Nonrenewable primary energy as energy carrier	MJ	1.54E+03	3.25	E+02 4.	72E+02	2.04E+02	2.61E+01
NRPRM	Nonrenewable primary energy as material utilization	MJ	0.00E+00	0.00	E+00 0.	00E+00	0.00E+00	0.00E+00
SM	Use of secondary material	kg	0.00E+00	0.00	E+00 0.	00E+00	0.00E+00	0.00E+00
RSF	Use of renewable secondary fuels	MJ	0.00E+00	0.00	E+00 0.	00E+00	0.00E+00	0.00E+00
NRSF	Use of nonrenewable secondary fuels	MJ	0.00E+00	0.00	E+00 0.	00E+00	0.00E+00	0.00E+00
RE	Energy recovered from disposed waste	MJ	0.00E+00	0.00	E+00 0.	00E+00	0.00E+00	0.00E+00
FW	Use of net fresh water	m ³	1.29E+00	0.00	E+00 8	.66E-02	1.80E-02	4.65E-02
				Us	se	Dis	oosal	Total
	Primary and Secondary Resource Categories	L	Unit E	Us 32	se B4	Dis C2	oosal C4	Total
RPRE	Primary and Secondary Resource Categories Renewable primary energy as energy carrier		Unit E MJ 1.17	Us 3 2 E+01	B4 3.74E+02	Dis C2 0.00E+00	C4 1.36E-01	Total 4.27E+02
RPRE RPRM	Primary and Secondary Resource Categories Renewable primary energy as energy carrier Renewable primary energy resources as material utilization	n	Unit E MJ 1.17 MJ 1.41	Us 32 E+01 E+02	B4 3.74E+02 2.60E+03	Dis C2 0.00E+00 0.00E+00	C4 1.36E-01 6.78E-02	Total 4.27E+02 2.97E+03
RPRE RPRM NRPRE	Primary and Secondary Resource Categories Renewable primary energy as energy carrier Renewable primary energy resources as material utilization Nonrenewable primary energy as energy carrier	n	Unit _E MJ 1.17 MJ 1.41 MJ 2.00	Us 32 E+01 E+02 E+02	B4 3.74E+02 2.60E+03 1.96E+04	Dis C2 0.00E+00 0.00E+00 1.28E+01	C4 1.36E-01 6.78E-02 1.32E+01	Total 4.27E+02 2.97E+03 2.24E+04
RPRE RPRM NRPRE NRPRM	Primary and Secondary Resource Categories Renewable primary energy as energy carrier Renewable primary energy resources as material utilization Nonrenewable primary energy as energy carrier Nonrenewable primary energy as material utilization	n	Unit E MJ 1.17 MJ 1.41 MJ 2.00 MJ 0.000	Us 52 E+01 E+02 E+02 E+00	B4 3.74E+02 2.60E+03 1.96E+04 0.00E+00	Dis C2 0.00E+00 0.00E+00 1.28E+01 0.00E+00	C4 1.36E-01 6.78E-02 1.32E+01 0.00E+00	Total 4.27E+02 2.97E+03 2.24E+04 0.00E+00
RPRE RPRM NRPRE NRPRM SM	Primary and Secondary Resource Categories Renewable primary energy as energy carrier Renewable primary energy resources as material utilization Nonrenewable primary energy as energy carrier Nonrenewable primary energy as material utilization Use of secondary material	1	Unit E MJ 1.17 MJ 1.41 MJ 2.00 MJ 0.00 kg 0.00	Us 52 E+01 E+02 E+02 E+00 E+00 E+00	B4 3.74E+02 2.60E+03 1.96E+04 0.00E+00 0.00E+00	Dis C2 0.00E+00 0.00E+00 1.28E+01 0.00E+00 0.00E+00	C4 1.36E-01 6.78E-02 1.32E+01 0.00E+00 0.00E+00	Total 4.27E+02 2.97E+03 2.24E+04 0.00E+00 0.00E+00
RPRE RPRM NRPRE NRPRM SM RSF	Primary and Secondary Resource Categories Renewable primary energy as energy carrier Renewable primary energy resources as material utilization Nonrenewable primary energy as energy carrier Nonrenewable primary energy as material utilization Use of secondary material Use of renewable secondary fuels	1	Unit E MJ 1.17 MJ 1.41 MJ 2.00 MJ 0.00 kg 0.00 MJ 0.00	Us 32 E+01 E+02 E+02 E+00 E+00 E+00	B4 3.74E+02 2.60E+03 1.96E+04 0.00E+00 0.00E+00 0.00E+00	Dis C2 0.00E+00 0.00E+00 1.28E+01 0.00E+00 0.00E+00 0.00E+00	C4 1.36E-01 6.78E-02 1.32E+01 0.00E+00 0.00E+00 0.00E+00	Total 4.27E+02 2.97E+03 2.24E+04 0.00E+00 0.00E+00 0.00E+00
RPRE RPRM NRPRE NRPRM SM RSF NRSF	Primary and Secondary Resource Categories Renewable primary energy as energy carrier Renewable primary energy resources as material utilization Nonrenewable primary energy as energy carrier Nonrenewable primary energy as material utilization Use of secondary material Use of renewable secondary fuels Use of nonrenewable secondary fuels	<u>ו</u>	Unit E MJ 1.17 MJ 1.41 MJ 2.00 MJ 0.00 kg 0.00 MJ 0.00 MJ 0.00	Us 32 E+01 E+02 E+02 E+00 E+00 E+00 E+00	B4 3.74E+02 2.60E+03 1.96E+04 0.00E+00 0.00E+00 0.00E+00	Dis C2 0.00E+00 1.28E+01 0.00E+00 0.00E+00 0.00E+00 0.00E+00	C4 1.36E-01 6.78E-02 1.32E+01 0.00E+00 0.00E+00 0.00E+00 0.00E+00	Total 4.27E+02 2.97E+03 2.24E+04 0.00E+00 0.00E+00 0.00E+00 0.00E+00
RPRE RPRM NRPRE NRPRM SM SM RSF NRSF RE	Primary and Secondary Resource Categories Renewable primary energy as energy carrier Renewable primary energy resources as material utilization Nonrenewable primary energy as energy carrier Nonrenewable primary energy as material utilization Use of secondary material Use of secondary material Use of renewable secondary fuels Use of nonrenewable secondary fuels Energy recovered from disposed waste	1	Unit E MJ 1.17 MJ 1.41 MJ 2.00 MJ 0.00 kg 0.00 MJ 0.00 MJ 0.00 MJ 0.00 MJ 0.00 MJ 0.00	Us 22 E+01 E+02 E+02 E+00 E+00 E+00 E+00 E+00 E+00	B4 3.74E+02 2.60E+03 1.96E+04 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00	Dis C2 0.00E+00 0.00E+00 1.28E+01 0.00E+00 0.00E+00 0.00E+00 0.00E+00	C4 1.36E-01 6.78E-02 1.32E+01 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00	Total 4.27E+02 2.97E+03 2.24E+04 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00 0.00E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Table 32 - Viatera Minimum Use of Primary and Secondary Resources

		Unit	Raw Material t Acquisition		C	onstruction	Install		
	Primary and Secondary Resource Categories		ŀ	\1	A	2	A3	A4	A5
RPRE	Renewable primary energy as energy carrier	MJ	2.25	E+01	0.00E	E+00	3.03E+00	1.31E+00	1.06E+00
RPRM	Renewable primary energy resources as material utilization	MJ	1.92	E+01	0.00E	E+00	2.01E+02	4.59E-01	7.43E-01
NRPRE	Nonrenewable primary energy as energy carrier	MJ	9.72	E+02	3.40E	E+02	4.72E+02	2.04E+02	2.63E+01
NRPRM	Nonrenewable primary energy as material utilization	MJ	0.00	E+00	0.00E	E+00	0.00E+00	0.00E+00	0.00E+00
SM	Use of secondary material	kg	0.00	E+00	0.00E	E+00	0.00E+00	0.00E+00	0.00E+00
RSF	Use of renewable secondary fuels	MJ	0.00	E+00	0.00E	E+00	0.00E+00	0.00E+00	0.00E+00
NRSF	Use of nonrenewable secondary fuels	MJ	0.00	E+00	0.00E	E+00	0.00E+00	0.00E+00	0.00E+00
RE	Energy recovered from disposed waste	MJ	0.00	E+00	0.00E	E+00	0.00E+00	0.00E+00	0.00E+00
FW	Use of net fresh water	m ³	8.07	'E-01	0.00E	E+00	8.66E-02	1.80E-02	4.66E-02
					Us	е	Dis	posal	Total
	Primary and Secondary Resource Categories		Unit	B	2	B4	C2	C4	TOtal
RPRE	Renewable primary energy as energy carrier		MJ	1.17E	+01	2.78E+0	2 0.00E+00	1.36E-01	3.18E+02
RPRM	Renewable primary energy resources as material utilization	۱	MJ	1.41E	+02	2.54E+0	3 0.00E+00	6.78E-02	2.90E+03
NRPRE	Nonrenewable primary energy as energy carrier		MJ	2.00E	+02	1.56E+0	4 2.85E-01	1.32E+01	1.78E+04
NRPRM	Nonrenewable primary energy as material utilization		MJ	0.00E	+00	0.00E+0	0 0.00E+00	0.00E+00	0.00E+00
SM	Use of secondary material		kg	0.00E	+00	0.00E+0	0 0.00E+00	0.00E+00	0.00E+00
RSF	Use of renewable secondary fuels		MJ	0.00E	+00	0.00E+0	0 0.00E+00	0.00E+00	0.00E+00
NRSF	Use of nonrenewable secondary fuels		MJ	0.00E	+00	0.00E+0	0 0.00E+00	0.00E+00	0.00E+00
RE	Energy recovered from disposed waste		MJ	0.00E	+00	0.00E+0	0 0.00E+00	0.00E+00	0.00E+00
FW	Use of net fresh water		m ³	2.66E	+00	2.55E+0	1 0.00E+00	2.44E-02	2.91E+01

Additionally, the resource use for all stages of the life cycle of the HIMACS and Viatera products were differentiated by resources type, as shown below in Tables 33 through 36.

Table 33 – HIMACS Maximum Emissions and Removals of CO2

			Raw M Acqui	aterial Construction		Install	
	missions and Removals of CO2 Categories		A1	A2	A3	A4	A5
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+00	0.00E+00	3.03E-02	0.00E+00	0.00E+00
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.03E-02

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Unit	Raw Material Acquisition		Construction	Ins	tall
E	missions and Removals of CO2 Categories		A1	A2	A3	A4	A5
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
		Unit		Use	Dispo	sal	Total
E	missions and Removals of CO2 Categories	Onic	B2	B4	C2	C4	Total
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+0	2.12E-01	0.00E+00	0.00E+00	2.42E-01
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+0	2.12E-01	0.00E+00	0.00E+00	2.42E-01
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO ₂	0.00E+0	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 34 – HIMACS Minimum Emissions and Removals of CO₂

		Unit	Raw Material Acquisition		Construction	Install	
E	missions and Removals of CO2 Categories		A1	A2	A3	A4	A5
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+00	0.00E+00	6.74E-03	0.00E+00	0.00E+00
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	6.74E-03
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Unit	Raw Material Acquisition		Construction	Ins	tall
E	missions and Removals of CO2 Categories		A1	A2	A3	A4	A5
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
		Unit		Use	Dispo	sal	Total
E	missions and Removals of CO2 Categories	Onic	B2	B4	C2	C4	lotai
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+00	4.72E-02	0.00E+00	0.00E+00	5.39E-02
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+00	4.72E-02	0.00E+00	0.00E+00	5.39E-02
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 35 – Viatera Maximum Emissions and Removals of CO2

		Unit	Acquisition		Construction	Ins	tall
	missions and Removals of CO2 Categories		A1	A2	A3	A4	A5
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+00	0.00E+00	2.36E-02	0.00E+00	0.00E+00
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.36E-02
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
		Unit		Use	Dispo	osal	Total
E	missions and Removals of CO2 Categories		B2	B4	C2	C4	
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Unit	Raw Material C Unit Acquisition		Construction	Install	
	missions and Removals of CO2 Categories		A1	A2	A3	A4	A5
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+00	1.65E-01	0.00E+00	0.00E+00	1.89E-01
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+00	1.65E-01	0.00E+00	0.00E+00	1.89E-01
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 36 - Viatera Minimum Emissions and Removals of CO₂

		Unit	Raw Material Acquisition		Construction	Ins	tall
E	missions and Removals of CO2 Categories		A1	A2	A3	A4	A5
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+00	0.00E+00	2.36E-02	0.00E+00	0.00E+00
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	2.36E-02
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
		Unit		Use	Dispo	sal	Total
E	missions and Removals of CO2 Categories	Onic	B2	B4	C2	C4	Total
BCRP	Biogenic Carbon Removal from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCEP	Biogenic Carbon Emissions from Product	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
BCRK	Biogenic Carbon Removal from Packaging	kg CO ₂	0.00E+00	1.65E-01	0.00E+00	0.00E+00	1.89E-01
BCEK	Biogenic Carbon Emissions from Packaging	kg CO ₂	0.00E+00	1.65E-01	0.00E+00	0.00E+00	1.89E-01
BCEW	Biogenic Carbon Emissions from Combustion of Waste from Renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org





HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Unit	Raw Ma Acquis	aterial sition	Construction	Ins	tall
E	Emissions and Removals of CO2 Categories		A1	A2	A3	A4	A5
CCE	Calcination Carbon Emissions	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CCR	Carbonation Carbon Removal	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CWNR	Carbon Emissions from Combustion of Waste from Non-renewable Sources Used in Production Process	kg CO ₂	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

The disposal of waste throughout the product life cycle is classified as either hazardous or non-hazardous waste. This inventory data for both the HIMACS and Viatera product lines is included in Tables 37 through 40 below. These data are expressed in mass per functional unit.

Table 37 – HIMACS Maximum Waste to Disposal												
		Unit	Raw M Acqui	laterial sition	Con	struction	Inst	all				
	Waste Categories		A1	A2		A3	A4	A5				
HWD	Hazardous waste disposed	kg	1.53E-04	0.00E+00	2.34E-05		1.13E-04	1.41E-05				
NHWD	Non-hazardous waste disposed	kg	1.28E+01	0.00E+00	8.	55E+00	3.99E+00	3.02E+00				
HLRW	High-level radioactive waste	kg	3.20E-04	0.00E+00	6.09E-05		3.10E-04	3.64E-05				
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00	0.00E+00	0.00E+00		0.00E+00	0.00E+00				
CRU	Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00		0.00E+00	0.00E+00				
MR	Materials for recycling	kg	0.00E+00	0.00E+00	0.00E+00		0.00E+00	4.56E-02				
MER	Materials for energy recovery	kg	0.00E+00	0.00E+00	0.	00E+00	0.00E+00	3.71E-03				
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E+00	0.	00E+00	0.00E+00	0.00E+00				
		Unit		Use		Dis	oosal	Total				
	Waste Categories	Onit	B2	B4		C2	C4	Total				
HWD	Hazardous waste disposed	kg	3.33E-02	2.35E	-01	0.00E+00	7.32E-06	2.68E-01				
NHWD	Non-hazardous waste disposed	kg	1.31E+01	4.02E-	+02	0.00E+00	1.60E+01	4.59E+02				
HLRW	High-level radioactive waste	kg	5.96E-04	9.40E	-03	0.00E+00	1.92E-05	1.07E-02				
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00	0.00E-	+00	0.00E+00	0.00E+00	0.00E+00				
CRU	Components for re-use	kg	0.00E+00	0.00E-	+00	0.00E+00	0.00E+00	0.00E+00				
MR	Materials for recycling		0.00E+00	3.19E	01	0.00E+00	0.00E+00	3.65E-01				
MER	Materials for energy recovery	kg	0.00E+00	2.81E-	+01	0.00E+00	4.01E+00	3.21E+01				
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E-	+00	0.00E+00	0.00E+00	0.00E+00				

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Table 38 - HIMACS Minimum Waste to Disposal												
		Unit	Raw M Acqui	aterial sition	Con	struction	Inst	all				
	Waste Categories		A1	A2		A3	A4	A5				
HWD	Hazardous waste disposed	kg	1.21E-04	0.00E+00	3.	03E-05	1.53E-04	1.42E-05				
NHWD	Non-hazardous waste disposed	kg	9.27E+00	0.00E+00	1.:	38E+00	4.79E+00	3.06E+00				
HLRW	High-level radioactive waste	kg	3.74E-04	0.00E+00	4.	17E-04	5.46E-04	3.65E-05				
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00	0.00E+00	0.0	00E+00	0.00E+00	0.00E+00				
CRU	Components for re-use	kg	0.00E+00	0.00E+00	0.0	00E+00	0.00E+00	0.00E+00				
MR	Materials for recycling	kg	0.00E+00	0.00E+00	0.0	00E+00	0.00E+00	4.56E-02				
MER	Materials for energy recovery	kg	0.00E+00	0.00E+00	0.0	00E+00	0.00E+00	3.71E-03				
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E+00	0.0	00E+00	0.00E+00	0.00E+00				
		Unit		Use		Disp	oosal	Total				
	Waste Categories		B2	B4		C2	C4					
HWD	Hazardous waste disposed	kg	3.33E-02	2.35E-	·01	0.00E+00	7.32E-06	2.69E-01				
NHWD	Non-hazardous waste disposed	kg	1.31E+01	3.33E+	-02	0.00E+00	1.60E+01	5.85E+01				
HLRW	High-level radioactive waste	kg	5.96E-04	1.39E-	02	0.00E+00	1.92E-05	1.59E-02				
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00	0.00E+	-00	0.00E+00	0.00E+00	0.00E+00				
CRU	Components for re-use	kg	0.00E+00	0.00E+	-00	0.00E+00	0.00E+00	0.00E+00				
MR	Materials for recycling		0.00E+00	3.19E-	·01	0.00E+00	0.00E+00	3.65E-01				
MER	Materials for energy recovery		0.00E+00	2.81E+	·01 0.00E+00		4.01E+00	3.21E+01				
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E+	-00	0.00E+00	0.00E+00	0.00E+00				

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Unit	Raw Material it Acquisition		Construction		Ins	tall
	Waste Categories		A1	A2		A3	A4	A5
HWD	Hazardous waste disposed	kg	7.15E-04	0.00E+00	7.	98E-05	3.91E-04	2.30E-05
NHWD	Non-hazardous waste disposed	kg	7.58E+00	0.00E+00	4.	81E+01	1.38E+01	1.00E+01
HLRW	High-level radioactive waste	kg	1.77E-03	0.00E+00	2.	12E-04	1.07E-03	4.94E-05
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00	0.00E+00	0.	00E+00	0.00E+00	0.00E+00
CRU	Components for re-use	kg	0.00E+00	0.00E+00	0.	00E+00	0.00E+00	0.00E+00
MR	Materials for recycling	kg	0.00E+00	0.00E+00	0.	00E+00	0.00E+00	3.54E-02
MER	Materials for energy recovery	kg	0.00E+00	0.00E+00	0.	00E+00	0.00E+00	3.81E-03
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E+00	0.	00E+00	0.00E+00	0.00E+00
		Unit		Use		Dis	posal	Total
	Waste Categories	Onic	B2	B4		C2	C4	i otai
HWD	Hazardous waste disposed	kg	3.33E-02	2.41E	-01	0.00E+00	2.53E-05	2.76E-01
NHWD	Non-hazardous waste disposed	kg	1.31E+01	1.06E+	+03	0.00E+00	5.92E+01	1.21E+03
HLRW	High-level radioactive waste	kg	5.96E-04	2.64E	-02	0.00E+00	6.65E-05	3.01E-02
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00) 0.00E+	+00	0.00E+00	0.00E+00	0.00E+00
CRU	Components for re-use	kg	0.00E+00	0.00E+	+00	0.00E+00	0.00E+00	0.00E+00
MR	Materials for recycling	kg	0.00E+00) 2.48E·	-01	0.00E+00	0.00E+00	2.83E-01
MER	Materials for energy recovery	kg	0.00E+00	9.70E+	+01	0.00E+00	1.39E+01	1.11E+02
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E+	+00	0.00E+00	0.00E+00	0.00E+00

Table 39 – Viatera Maximum Waste to Disposal

Table 40 - Viatera Minimum Waste to Disposal

		Unit	Raw Material it Acquisition		Construction	Install	
	Waste Categories		A1	A2	A3	A4	A5
HWD	Hazardous waste disposed	kg	4.75E-04	0.00E+00	7.98E-05	3.91E-04	2.34E-05
NHWD	Non-hazardous waste disposed	kg	5.24E+00	0.00E+00	4.81E+01	1.38E+01	1.03E+01
HLRW	High-level radioactive waste	kg	1.21E-03	0.00E+00	2.12E-04	1.07E-03	4.99E-05
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CRU	Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MR	Materials for recycling	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.54E-02
MER	Materials for energy recovery	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	3.81E-03
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Unit	Use t		Disposal		Total
	Waste Categories		B2	B4	C2	C4	
HWD	Hazardous waste disposed	kg	3.33E-02	2.40E-01	0.00E+00	2.53E-05	2.74E-01
NHWD	Non-hazardous waste disposed	kg	1.31E+01	1.05E+03	0.00E+00	5.92E+01	1.20E+03
HLRW	High-level radioactive waste	kg	5.96E-04	2.24E-02	0.00E+00	6.65E-05	2.56E-02
ILLRW	Intermediate- and low-level radioactive waste	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CRU	Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MR	Materials for recycling	kg	0.00E+00	2.48E-01	0.00E+00	0.00E+00	2.83E-01
MER	Materials for energy recovery	kg	0.00E+00	9.70E+01	0.00E+00	1.39E+01	1.11E+02
EE	Recovered energy exported from product system	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Lastly, ISO 21930 requires life cycle impact assessment data to be presented. LCIA data using both TRACI 2.1 and CML methodologies are presented below.

TRACI 2.1

Tables 41 through 44 below represent the cradle to grave life cycle impact assessment results for the HIMACS and Viatera products according to the TRACI 2.1 impact assessment methodology.

Table 41 – HIMACS Maximum TRACI 2.1 Cradle to Grave LCIA											
Impact Category	Unit	Raw Ma Unit Acquis	Raw Material Co Acquisition uo		Install		U	se	Disposal		Total
Category		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO₂ eq	6.96E+01	8.82E+00	1.40E+01	3.45E+00	2.90E+00	4.42E+01	1.02E+03	2.43E-01	2.16E+00	1.16E+03
Acidification	kg SO ₂ eq	3.49E-01	9.83E-02	1.16E-01	1.36E-02	6.42E-03	1.50E-01	5.17E+00	3.21E-03	1.88E-03	5.91E+00
Smog	kg O₃ eq	3.63E+00	2.81E+00	7.37E-01	1.88E-01	9.60E-02	1.88E+00	6.63E+01	8.23E-02	4.99E-02	7.58E+01
Eutroph- ication	kg N eq	1.25E-01	5.37E-03	5.81E-03	3.07E-03	2.16E-02	2.47E+00	1.84E+01	1.94E-04	2.91E-03	2.11E+01
Ozone Depletion	kg CFC₋ ₁1 eq	1.59E-06	3.35E-10	1.65E-07	7.29E-07	7.04E-07	2.71E-06	4.17E-05	1.03E-11	5.09E-08	4.77E-05
Fossil Fuel Depletion	MJ surplus	1.48E+02	1.58E+01	1.75E+01	7.00E+00	2.07E+00	1.19E+01	1.42E+03	4.85E-01	4.54E-01	1.63E+03

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Table 42 - HIMACS Minimum TRACI 2.1 Cradle to Grave LCIA

Impact Catagory	Unit	Raw Material Acquisition		Constr- uction	Install		Use		Disposal		Total
Calegory		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO ₂ eq	5.40E+01	1.03E+00	4.54E+00	5.52E+00	2.55E+00	4.42E+01	8.00E+02	2.43E-01	2.16E+00	9.14E+02
Acidification	kg SO ₂ eq	2.81E-01	1.05E-02	2.76E-02	5.55E-02	6.17E-03	1.50E-01	3.75E+00	3.21E-03	1.88E-03	4.29E+00
Smog	kg O₃ eq	2.83E+00	2.82E-01	2.28E-01	8.57E-01	9.06E-02	1.88E+00	4.41E+01	8.23E-02	4.99E-02	5.04E+01
Eutroph- ication	kg N eq	9.15E-02	7.37E-04	2.69E-02	7.07E-03	1.78E-02	2.47E+00	1.83E+01	1.94E-04	2.91E-03	2.09E+01
Ozone Depletion	kg CFC- 11 eq	1.35E-06	5.73E-08	1.61E-07	1.26E-06	7.02E-07	2.71E-06	4.40E-05	1.03E-11	5.09E-08	5.03E-05
Fossil Fuel Depletion	MJ surplus	1.12E+02	1.92E+00	4.04E+00	1.07E+01	2.03E+00	1.19E+01	1.01E+03	4.85E-01	4.54E-01	1.15E+03

Table 43 – Viatera Maximum TRACI 2.1 Cradle to Grave LCIA

Impact	Unit	Raw Material Unit Acquisition		Constr- uction Install		U	se	Disp	osal	Total	
Calegory		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO ₂ eq	8.64E+01	2.40E+01	2.88E+01	1.19E+01	7.16E+00	4.41E+01	1.47E+03	8.40E-01	7.48E+00	1.69E+03
Acidification	kg SO₂ eq	3.16E-01	2.94E-01	2.26E-01	4.70E-02	9.35E-03	1.50E-01	7.31E+00	3.55E-11	1.76E-07	8.35E+00
Smog	kg O₃ eq	4.19E+00	8.46E+00	1.64E+00	6.49E-01	1.60E-01	1.88E+00	1.19E+02	1.11E-02	6.51E-03	1.36E+02
Eutroph- ication	kg N eq	2.34E-01	1.61E-02	2.14E-02	1.06E-02	6.71E-02	2.47E+00	1.98E+01	6.69E-04	1.01E-02	2.26E+01
Ozone Depletion	kg CFC- 11 eq	9.77E-06	9.10E-10	8.17E-07	2.52E-06	7.35E-07	2.71E-06	3.20E+00	2.85E-01	1.73E-01	3.66E+00
Fossil Fuel Depletion	MJ surplus	1.61E+02	4.30E+01	3.99E+01	2.42E+01	2.57E+00	1.19E+01	2.00E+03	1.68E+00	1.57E+00	2.29E+03

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Impact	Unit	Raw Mat Unit Acquisi		aw Material Constr- Acquisition uction		Install		se	Disp	Total	
Category		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO ₂ eq	5.49E+01	2.50E+01	2.88E+01	1.19E+01	7.32E+00	4.42E+01	1.26E+03	8.40E-01	7.48E+00	1.44E+03
Acidification	kg SO ₂ eq	2.08E-01	3.10E-01	2.26E-01	4.70E-02	9.46E-03	1.50E-01	6.78E+00	1.11E-02	6.51E-03	7.74E+00
Smog	kg O₃ eq	2.79E+00	8.91E+00	1.64E+00	6.49E-01	1.63E-01	1.88E+00	1.15E+02	2.85E-01	1.73E-01	1.32E+02
Eutroph- ication	kg N eq	1.51E-01	1.69E-02	2.15E-02	1.06E-02	6.88E-02	2.47E+00	1.92E+01	6.69E-04	1.01E-02	2.20E+01
Ozone Depletion	kg CFC- 11 eq	6.27E-06	9.50E-10	8.17E-07	2.52E-06	7.36E-07	2.71E-06	9.27E-05	3.55E-11	1.76E-07	1.06E-04
Fossil Fuel Depletion	MJ surplus	1.01E+02	4.49E+01	3.99E+01	2.42E+01	2.58E+00	1.19E+01	1.60E+03	1.68E+00	1.57E+00	1.82E+03

Table 44 – Viatera Minimum TRACI 2.1 Cradle to Grave LCIA

CML

In addition to the LCIA results reported above using the TRACI 2.1 methodology, LCIA results were also calculated using the CML impact assessment methodology. Tables 45 through 48 below represent the cradle to grave life cycle impact assessment results for the HIMACS and Viatera products according to the CML impact assessment methodology.

Table 45 – HIMACS Maximum CML Cradle to Grave LCIA

Impact	Unit	Raw Material Unit Acquisition		Construc- tion Install			U	se	Disp	osal	Total
Category		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO₂ eq	7.08E+01	8.84E+00	1.42E+01	3.46E+00	3.24E+00	4.47E+01	1.03E+03	2.44E-01	2.16E+00	1.18E+03
Acidification	kg SO ₂ eq	3.65E-01	7.95E-02	1.27E-01	1.34E-02	6.00E-03	1.34E-01	5.10E+00	2.46E-03	1.52E-03	5.83E+00
Photochemical Ozone Creation	kg C ₂ H ₄ eq	2.83E-02	2.42E-03	5.64E-03	6.41E-04	5.90E-04	2.67E-02	4.46E-01	-5.24E-04	5.29E-05	5.10E-01
Eutrophication	kg PO₄ eq	6.30E-02	1.49E-02	5.53E-03	1.99E-03	8.66E-03	1.06E+00	8.11E+00	5.37E-04	1.36E-03	9.27E+00
Ozone Depletion	kg CFC- 11 eq	1.37E-06	3.32E-10	1.32E-07	5.47E-07	6.86E-07	2.47E-06	3.67E-05	1.02E-11	3.93E-08	4.19E-05

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Impact	Unit	Raw M Acqui	laterial sition	Construc- tion	Ins	tall	U	se	Disp	osal	Total
Category		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Abiotic Depletion (elements)	kg Sb eq	1.56E-04	0.00E+00	1.08E-05	6.98E-06	9.77E-06	3.46E-04	3.71E-03	0.00E+00	5.67E-07	4.24E-03
Abiotic Depletion (fossil fuel)	MJ	1.11E+03	1.13E+02	2.07E+02	5.50E+01	1.86E+01	1.40E+02	1.15E+04	3.49E+00	3.51E+00	1.32E+04

Table 46 - HIMACS Minimum CML Cradle to Grave LCIA

Impact	Unit	Raw Material Acquisition		Construc- tion	Install		Use		Disp	osal	Total
Category		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO₂ eq	5.50E+01	1.05E+00	4.59E+00	5.58E+00	3.28E+00	4.47E+01	8.16E+02	2.44E-01	2.16E+00	9.33E+02
Acidification	kg SO ₂ eq	2.96E-01	8.83E-03	2.95E-02	5.49E-02	6.01E-03	1.34E-01	3.73E+00	2.46E-03	1.52E-03	4.26E+00
Photochemical Ozone Creation	kg C ₂ H ₄ eq	2.78E-02	2.73E-04	1.67E-03	1.82E-03	5.95E-04	2.67E-02	4.09E-01	-5.24E-04	5.29E-05	4.67E-01
Eutrophication	kg PO₄ eq	4.83E-02	1.58E-03	1.22E-02	6.65E-03	8.78E-03	1.06E+00	8.00E+00	5.37E-04	1.36E-03	9.14E+00
Ozone Depletion	kg CFC- 11 eq	1.15E-06	4.29E-08	1.30E-07	9.43E-07	6.86E-07	2.47E-06	3.82E-05	1.02E-11	3.93E-08	4.37E-05
Abiotic Depletion (elements)	kg Sb eq	1.04E-04	5.19E-07	2.12E-05	9.28E-06	9.77E-06	3.46E-04	3.44E-03	0.00E+00	5.67E-07	3.93E-03
Abiotic Depletion (fossil fuel)	MJ	8.39E+02	1.39E+01	5.63E+01	8.18E+01	1.86E+01	1.40E+02	8.10E+03	3.49E+00	3.51E+00	9.25E+03

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

		Table 47 – Viatera Maximum CML Cradle to Grave LCIA									
Impact	Unit	Raw Material Acquisition		Construc- tion	Install		Use		Disposal		Total
Calegory		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO₂ eq	8.52E+01	2.40E+01	2.91E+01	1.20E+01	8.30E+00	4.47E+01	1.48E+03	7.47E+00	8.44E-01	1.69E+03
Acidification	kg SO₂ eq	3.12E-01	2.38E-01	2.44E-01	4.65E-02	8.29E-03	1.34E-01	6.97E+00	5.25E-03	8.49E-03	7.97E+00
Photochemical Ozone Creation	kg C ₂ H ₄ eq	3.69E-02	6.83E-03	1.19E-02	2.22E-03	1.27E-03	2.67E-02	5.89E-01	1.83E-04	-1.81E-03	6.73E-01
Eutrophication	kg PO₄ eq	1.18E-01	4.46E-02	1.54E-02	6.90E-03	2.61E-02	1.06E+00	8.96E+00	4.70E-03	1.86E-03	1.02E+01
Ozone Depletion	kg CFC- 11 eq	8.88E-06	9.01E-10	7.17E-07	1.89E-06	7.09E-07	2.47E-06	1.04E-04	1.36E-07	3.51E-11	1.18E-04
Abiotic Depletion (elements)	kg Sb eq	8.03E-04	0.00E+00	3.71E-05	2.41E-05	1.04E-05	3.46E-04	8.56E-03	1.96E-06	0.00E+00	9.78E-03
Abiotic Depletion (fossil fuel)	MJ	1.37E+03	3.07E+02	4.39E+02	1.90E+02	2.26E+01	1.40E+02	1.74E+04	1.21E+01	1.21E+01	1.99E+04

Table 48 - Viatera Minimum CML Cradle to Grave LCIA

Impact Category	Unit	Raw Material Acquisition		Construc- tion	Install		Use		Disposal		Total
		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Global Warming	kg CO₂ eq	5.42E+01	2.51E+01	2.91E+01	1.20E+01	8.48E+00	4.47E+01	1.27E+03	8.44E-01	7.47E+00	1.45E+03
Acidification	kg SO ₂ eq	2.04E-01	2.50E-01	2.44E-01	4.65E-02	8.37E-03	1.34E-01	6.30E+00	8.49E-03	5.25E-03	7.20E+00
Photochemical Ozone Creation	kg C ₂ H ₄ eq	2.60E-02	7.15E-03	1.19E-02	2.22E-03	1.30E-03	2.67E-02	5.15E-01	-1.81E- 03	1.83E-04	5.89E-01
Eutrophication	kg PO₄ eq	7.50E-02	4.70E-02	1.54E-02	6.90E-03	2.67E-02	1.06E+00	8.68E+00	1.86E-03	4.70E-03	9.92E+00

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org



HIMACS and Viatera by LX Hausys

Featured Product: HIMACS Eden Plus Collection

Impact Category	Unit	Raw Material Acquisition		Construc- tion	Install		Use		Disposal		Total
		A1	A2	A3	A4	A5	B2	B4	C2	C4	
Ozone Depletion	kg CFC- 11 eq	5.66E-06	9.41E-10	7.17E-07	1.89E-06	7.10E-07	2.47E-06	8.11E-05	3.51E-11	1.36E-07	9.26E-05
Abiotic Depletion (elements)	kg Sb eq	4.97E-04	0.00E+00	3.71E-05	2.41E-05	1.04E-05	3.46E-04	6.42E-03	0.00E+00	1.96E-06	7.33E-03
Abiotic Depletion (fossil fuel)	MJ	8.61E+02	3.20E+02	4.39E+02	1.90E+02	2.27E+01	1.40E+02	1.40E+04	1.21E+01	1.21E+01	1.60E+04

For additional information about the HIMACS and Viatera product lines, please visit <u>www.lxhausys.com</u>. To contact LX Hausys, please visit <u>https://www.lxhausys.com/us/contactUs/pro</u>.

EPD Program Operator NSF International 789 N. Dixboro Rd. Ann Arbor, MI 48105 USA www.nsfsustainability.org

